


2010 Shaft Models

Alloy/Carbon		Materials/Construction	Inserts	Points	Nock System	Nock Type	Weight Tolerance ⁴	Straightness ¹	Color/Finish	Sizes	
		High-strength carbon fiber bonded to a precision 7075 alloy core tube—barreled shaft	Not Available	X10 Ballistic Tungsten Break-off or X10 Stainless Steel Break-off	X10 Pin	Pin Nocks	±0.5 grains	±.0015" guaranteed	Polished Black Carbon	1000, 900, 830, 750, 700, 650, 600, 550, 500, 450, 410, 380	
X10 PROTOUR™		High-strength carbon fiber bonded to a precision 7075 alloy core tube—single-taper shaft	Not Available	X10 Ballistic Tungsten Break-off or X10 Stainless Steel Break-off	X10 or ProTour Pin	Pin Nocks	±0.5 grains	±.0015" guaranteed	Polished Black Carbon	770, 720, 670, 620, 570, 520, 470, 420, 380	
A/C/E.		High-strength carbon fiber bonded to a precision 7075 alloy core tube—barreled shaft	A/C/E Insert	Screw-in, One-piece or A/C/E Stainless Steel Break-off	A/C/E Pin or Insert Nock	Pin Nocks or G Nock	±0.5 grains	±.0015" guaranteed	Polished Black Carbon	(1250, 1100) ⁵ , 1000, 920, 850, 780, 720, 670, 620, 570, 520, 470, 430, 400, 370	
A/C/G™		High-strength carbon fiber bonded to a precision 7075 alloy core tube	A/C/E Insert	Screw-in, One-piece, A/C/E or A/C/G Stainless Steel Break-off	A/C/E & A/C/G Pin or Insert Nock	Pin Nocks or G Nock	±1 grain	±.002" guaranteed	Polished Black Carbon	1500, 1300, 1150, 1000, 880, 810, 710, 660, 610, 540, 480, 430	
A/C/C.		High-strength carbon fiber bonded to a precision 7075 alloy core tube	RPS Insert or Halfout Insert	One-piece Parabolic, NIBB, or RPS Point	UNI System	G Nock	±0.5 grains	±.002" guaranteed	Black, Micro-smooth Finish	2-00, 3L-00, 3-00, 2L-04, 2-04, 3X-04, 3L-04, 3-04, 3L-18, 3-18, 3-28, 3-39, 3-49, 3-60, 3-71	
Carbon		Materials/Construction	Inserts	Points	Nock System	Nock Type	Weight Tolerance ⁴	Straightness ²	Color/Finish	Sizes	
		SuperLite Carbon multi-layer wrapped fibers	RPS Insert	One-piece Bullet or RPS Point	Super or G Nock UNI System	3D Super Nock, Super Nock, or G Nock	±2 grains	±.003"	Black, Smooth-matte Finish	500, 400, 340	
		SuperLite Carbon multi-layer wrapped fibers	CB Insert	CB or RPS Point	UNI System	G Nock	±2 grains	±.001"	Black, Smooth-matte Finish	500, 400, 340	
		SuperLite Carbon multi-layer wrapped fibers	CB Insert	CB or RPS Point	UNI System	G Nock	±2 grains	±.003"	Black, Smooth-matte Finish	500, 400, 340	
N-FUSED Carbon		Materials/Construction	Inserts	Points	Nock System	Nock Type	Weight Tolerance ⁴	Straightness ²	Color/Finish	Sizes	
CARBONONE		UltraLite Nano N-FUSED carbon fibers	Not Available	Carbon One Stainless Steel Break-off	A/C/E Pin, Carbon One Pin, or insert Nock	Pin Nock, Pin G Nock, G Nock	±1 grains	±.003"	Black, Micro-smooth Finish	1150, 1000, 900, 810, 730, 660, 600	
Alloy		Aerospace Alloy	Strength ³ (psi)	Inserts	Points	Nock System	Nock Type	Weight Tolerance	Straightness ¹	Color Finish	Sizes
ECLIPSE™		7178-T9	105,000	Not Available	NIBB or One-piece Bullet	UNI or Super UNI System	3D Super Super Nock S Nock or G Nock	±3/4%	±.001" guaranteed	Hard-anodized Polished Blue, Polished Black	<i>1514, 1614, 1714, 1814, 1914, 2014, 2114, 2212, 2213, 2214, 2311, 2312, 2314, 2315, 2412, 2413, 2511, 2512, 2612, 2613, 2712</i>
PLATINUM PLUS®		7075-T9	96,000	RPS Insert	NIBB, One-piece Bullet, or RPS Point	UNI or Super UNI System	3D Super Super Nock or S Nock	±1%	±.002" guaranteed	Hard-anodized Platinum Grey	<i>1416, 1516, 1616, 1713, 1716, 1813, 1816, 1913, 1916, 2013, 2016, 2114, 2213, 2315</i>
Blues™		7075	90,000	RPS Insert 1716 & up	NIBB, One-piece Bullet, or RPS Point	Full-Diameter Taper Swage	Conventional	±2%	±.005" guaranteed	Hard-anodized Blue/Silver	1616, 1716, 1816, 1916, 2016
Jazz®		7075	90,000	RPS Insert 1716 & up	NIBB, One-piece Bullet, or RPS Point	Full-Diameter Taper Swage	Conventional or G Nock ⁶	±2%	±.005" guaranteed	Hard-anodized Purple/Silver	1214 ⁵ , 1413, 1416, 1516, 1616, 1716, 1816, 1916
Genesis™		7075	90,000	Not Available	One-piece Point	Full-Diameter Taper Swage	Conventional	±2.5 grains	±.005" guaranteed	Hard-anodized Bright Blue	1820
NEOS™		7075	90,000	Not Available	One-piece Point	Full-Diameter Taper Swage	Conventional	±5%	±.008" guaranteed	Hard-anodized Gold	1618

1 Guaranteed straight to more stringent standards than ATA/ASTM methods.
2 Guaranteed to meet or exceed similar carbon-industry straightness specifications.

3 Tensile strength value may vary ±3%.
4 Grains-per-shafts in a dozen bundle.
5 Special order only.
6 1214 size Jazz uses G Nock.

Eclipse and Platinum Plus sizes in italics use UNI System and G Nock.
®/™ Registered Trademark/Trademark of Easton.